

SLIMLINE 1U™ AUDIO OPTIONS

Rack Drawer Flip-up LCD Monitor/Keyboard/Trackball Configured for Multimedia Applications



In addition to its standard flip-up display with integral keyboard and trackball, our rugged SlimLine 1U features stereo speakers and a built-in headphone jack.

At only one rack unit high (1.75"), the compact design and industrial durability combine with General Digital's legendary configuration control and long product life cycles to create the ideal rack mount solution for network administration, telecommunications, mobile and tactical applications, and more.



SlimLine 1U audio options include a 3.5 mm headphone jack next to the trackball

FEATURES

- ▶ Standard LCDs available:
 - 17.3", 1920 x 1080 resolution
 - 19.0", 1280 x 1024 resolution
- ▶ Stereo speakers, audio amplifier, 3.5 mm headphone jack
- ▶ VGA, DVI-D and Composite video inputs
- ▶ Low profile occupies only 1U (1.75") of rack space
- ▶ Mounts directly to EIA-310 RETMA 19" racks via solid-bearing locking slides
- ▶ Rugged aluminum construction with durable finish is designed to be in compliance with MIL-DTL-901E, MIL-STD-810, MIL-STD-167 and more
- ▶ Designed, manufactured and serviced in the USA

OPTIONS

- ▶ Additional display sizes include 15.0" and 17.0"
- ▶ Compliance with radiated and conducted EMI requirements (e.g., MIL-STD-461, TEMPEST)
- ▶ Sunlight readable and NVIS-compatible display backlights
- ▶ Keyboard/trackball options: environmental sealing, colored keycaps and backlights, custom firmware and more
- ▶ Power supplies, DC-DC converters
- ▶ KVM switches, Smart Card (CAC) readers
- ▶ Extended warranties

Screenshot courtesy of Wind Vector/Shutterstock



SLIMLINE 1U™ AUDIO

SPECIFICATIONS

| | |
|-------------------------------------|---|
| Display Size | 17.3" / 19.0" |
| Resolution | 1920 x 1080 / 1280 x 1024 |
| Number of Colors | 16.7 Million |
| Luminance | 400 / 450 nits (standard display) |
| Contrast | 600:1 / 1000:1 |
| Viewing Angle (Horizontal/Vertical) | ±80/+60°, -80° / ±85°/+80° |
| Operating Temperature | 0° to 70°C / -30° to 85°C |
| Video Input | VGA, DVI-D, Component |
| Other | Stereo speakers, audio amplifier, 3.5 mm headphone jack |



60 Prestige Park Road

East Hartford, Connecticut 06108

Phone 860.282.2900 | Toll-Free 800.952.2535

E-mail gdc_info@generaldigital.com



General Digital is an SBA Small Business Concern

The appearance of U.S. Department of Defense (DoD) visual information does not imply or constitute DoD endorsement.

Information contained in this document is proprietary to General Digital Corporation and is current as of publication date. This document may not be modified in any way without the express written consent of General Digital. Product processing does not necessarily include testing of all parameters. General Digital reserves the right to change the configuration and performance of the product and to discontinue product at any time.

All product names are trademarks of their respective companies.

© 2026 GENERAL DIGITAL CORPORATION

999-0902-014r2